

FSF STAY OPEN FIRE DOOR

Advantages

Made in Canada for Canadian conditions

Rugged 2" curved slats

G90 Galvanized finish that needs no further painting

Structural Angle Guides and Bottom Bar are prime painted

Fluid governor for smooth and quiet operation

Steel Plate Brackets are more durable than stamped steel bracket plates

An economical alternative when a fire door is required to close only during testing or in the event of a fire

Resetting is simple and can be performed by one technician

Features

2C curved Slat Curtain, 22 ga.

¼" Thick Steel Bracket Plates

Cast Iron Stops

1 Year Warranty

¾, 1 ½, 3, or 4 hour fire labeled

Options

Prime painted hood

Optional solenoid release with 30 sec. time delay or 72HR battery backup

Smoke Detectors & sound strobes

Smoke seals

Benefits

Ease of installation and resetting



Ensures years of trouble free operation

Best value for the price





STAY OPEN FIRE DOOR DETAILS



TYPICAL DETAILS



GUIDE DETAILS



AREA CHART



DOOR CLEARANCE CHART

| Area | Slat | Dimensions in Inches | | | | | |
|------|------|----------------------|-----|----|--------|--------|--------|
| | | A | B | D | W | X | Y |
| 1 | 2C | 13" | 14" | 6" | 2 1/2" | 2 1/2" | 2 1/2" |
| 2 | 2C | 13" | 14" | 6" | 2 1/2" | 3" | 2 1/2" |

Available in sizes up to 13' 6" wide x 12' 0" high
Consult factory for oversize doors